

Fluids 2013-2015

FLUID CAPACITIES						
Fluid Type	Application	Standard	Metric	Fluid Spec	Note	S/H
Air Cond Compressor Oil		2.30 OZS.	0.1 L	PAG 46		S
Air Cond		1.05 LBS.	0.5 KG	HFC-134a (R-134a) Refrigerant		
Automatic Transmission Fluid	Drain and Refill	3.30 QTS.	3.1 L	ACURA Automatic Transmission Fluid DW-1	Use only ACURA ATF DW-1 (automatic transmission fluid). Do not mix with other transmission fluid. Using other than ACURA DW-1 may cause deterioration in transmission operation and durability, and could result in damage to the transmission.	S
Brake Fluid		N/A	N/A	ACURA Heavy Duty DOT 3 Brake Fluid		S
Differential Gear Oil	Drain and Refill,Rear	1.32 QTS.	1.2 L	ACURA All-Wheel Drive Fluid (DPSF)		S

Engine Coolant	Drain and Refill	1.75 GALS.	6.6 L	50/50 mix of HONDA Long-Life Antifreeze/Coolant reserve tank and Type 2 and distilled water	Includes: the coolant in the tank and that remaining in the engine.	S
Engine Oil	Drain and use S Refill,w/Filter	4.55 QTS.	4.3 L	Genuine ACURA Motor Oil API Premium-grade	You may also use synthetic motor oil if it is labeled with the API Certification Seal and is the specified viscosity grade.	S
Engine Oil	Drain and Refill,w/o Filter	4.23 QTS.	4 L	Genuine ACURA Motor Oil API Premium-grade SAE 0W-20 Detergent Oil.	You may also use synthetic motor oil if it is labeled with the API Certification Seal and is the specified viscosity grade.	S
Fuel Tank		16.00 GALS.	60.6 L			S
Transfer Case Fluid		0.43 QTS.	0.4 L	ACURA Hypoid Gear Oil HGO-Type1		S
Windshield Washer Fluid		2.60 QTS.	2.5 L		Use commercially-available windshield washer fluid only.	S