

SI 68624.  
CHAMPION.

**Front : Left**

Actual	Before	Specified Range
-0.4°		-1.0° 0.0°
		2.5° 4.0°
-0.13**		-0.08° 0.08°

Camber  
Caster  
Toe  
SAI  
Included Angle  
Turning Angle Diff.

**Front : Right**

Actual	Before	Specified Range
-0.5°		-1.0° 0.0°
		2.5° 4.0°
0.21**		-0.08° 0.08°

**Front**

Cross Camber  
Cross Caster  
Cross SAI  
Total Toe  
Cross Turn Diff.

Actual	Before	Specified Range
0.1°		-0.8° 0.8°
		-0.8° 0.8°
0.07°		-0.16° 0.16°

**Rear : Left**

Actual	Before	Specified Range
-1.0°		-1.5° -0.5°
0.23**		-0.08° 0.08°

Camber  
Toe

**Rear : Right**

Actual	Before	Specified Range
-1.6**		-1.5° -0.5°
0.02°		-0.08° 0.08°

**Rear**

Cross Camber  
Total Toe  
Thrust Angle

Actual	Before	Specified Range
0.6°		-0.8° 0.8°
0.24**		-0.16° 0.16°
0.11°		

\* This value is not within specification. Tire wear, handling and safety problems may result.