

IMPORTANT: PLEASE RETAIN THIS INSTRUCTION MANUAL FOR FUTURE REFERENCE



2009-11 Acura TL Overlay Mesh Grille A 27 HOP

Notes to the Technician:

E&G is proud to present this package to you and reminds you that for technical information, contact Lynn Eash or Lee Clary at 410-381-4900. Do not attempt installation any E&G product without first reading the detailed instructions. E&G Classics will not warrant damaged parts or vehicle due to altered installation instructions.

Copyright © 2010 by E&G Classics, Inc.


All right reserved. The reproduction or utilization of this work in any form or any electronic, mechanical, or other means, no known or hereafter invented, including xerography, photocopying, and recording, and in any information storage retrieval system is forbidden without written permission of owners.




Part #1402-0502-09U

Quantity	Description	Part No.
1	Mesh Grille ABS Surround	1402-0534-09U
1	Fine Mesh Insert	1402-0520-09
1	Hardware Kit (components listed below):	1402-1903-09
	(90") 1" Double Faced Tape	3004-9244-92
	(4) #8 x 1/2" Black Truss Head Screws	3999-9035-00
	(54") 1/8" x 1/4" Foam Tape	3999-9137-00
	(1) Emblem Backing Plate	1402-0158-09
	(2) 1.006"x .189"x .062" Black Plastic Washers	1999-0264-00
	(1) Bottom Foam Tape Location Template	1402-0068-09
	(1) Side Foam Tape Location Template	1402-0067-09

NOTE: Templates are on the last page of this instruction manual.



1. Remove the engine bay shroud by lifting straight up to release the clips and remove the cover (to be reinstalled).



2. Carefully apply several layers of masking tape around the painted grille surround to protect the factory paint.
3. Remove the top 10mm fasteners retaining the grille.

WARRANTY INFORMATION:

E&G Classics, Inc. warrants its chrome parts and products to be free from defects in material, workmanship or finish for Forty-Eight (48) months from the date of shipment by E&G. This warranty is limited to the repair or replacement, at E&G Classics option, of the defective part or product.

To obtain performance under this warranty you must:

- 1.) Present your E&G unit to an authorized distributor in your area with proof of purchase.
- 2.) If no distributor is available, contact E&G Classics (address below) for authorization to return unit.
- 3.) Returns - All unauthorized returns will be refused. Merchandise approved by E&G for return must have been purchased within the Forty-Eight (48) months. All returns require an authorization number obtained from E&G and the actual return must be accompanied by the written authorization form filled out completely. All merchandise must be inspected upon receipt and shortages reported within 48 hours. All merchandise must be in a resalable condition. Merchandise must be packed carefully in the original packing. If original packing is no longer usable, repack item(s) comparable to original manner. All returns are subject to a 25% handling charge. Special order items are not returnable. Defective merchandise must have an explanation of the problem. No credit will be issued unless invoice number and date of purchase has been supplied. Manufacturer shall be sole judge of defects in a product.
- 4.) UPS accounts - All returns must be prepaid. Do not send return shipments freight collect. Once E&G has made its decision and it is a claim against our warranty policy, E&G will credit incoming freight on damaged parts.
- 5.) No discontinued part or parts changed due to body style are returnable.

For Return Authorization, write or telephone: E&G Classics, Inc., 8910 McGaw Court, Columbia, MD 21045 (410) 381-4900 Attn.: Return Department.


You are responsible for inspecting all packages containing E&G Classics' parts and product immediately upon their receipt and must file a claim with the carrier for any damage disclosure by such inspection and notify E&G classics in writing at the above address of any such damage. This warranty does not extend to any of our products which have been subject to misuse, neglect, accident or have been altered or repaired in any way. This warranty does not cover any accidental or consequential damages for any breach of this warranty agreement. E&G Classics shall have no responsibility for any loss of time, inconvenience, commercial loss or consequential damage, nor shall E&G be liable for any injury or damage to persons or property by reason of any defect in material, workmanship or finish of its parts or products. This warranty gives you specific legal rights and you may also have other rights which may vary from state to state.



4. Pull the top of the factory grille towards you. Use a torx T-20 tool to remove the eight (8) torx screws holding the center section of the grille in place.




5. Once the eight (8) factory torx screws are removed, pull the grille insert forward and remove it from the grille surround.




6. Reinstall the upper 10mm mounting bolts removed in **Step 3**.




7. Reinstall the engine bay shroud removed in **Step 1** using the factory push pins.




8. Remove the factory Acura emblem from the factory grille. The emblem is attached with screws. Save the emblem and screws for reinstallation on the mesh grille.




9. Install the supplied black plastic washers and the factory screws to reinstall the factory emblem onto the mounting plate and mesh grille. Trim one or both of the washers so that they do not overlap. Apply dabs of silicone to the top and bottom of the emblem to help keep the emblem centered and level.




10. Align the mesh section into place (making sure it is tight against the lip the mesh will get screwed to) and use a 7/64" drill bit to drill through the top edge of the mesh and through the plastic factory grille for future truss head screw installation (4 places).




11. Cut out and align the supplied templates and tape them into place. Align a strip of masking tape to the front edges of the templates, then remove the templates, flip them over and repeat the procedure on the opposite side.




12. Align the supplied 1/8" x 1/4" foam tape with the edge of the masking tape as shown). Overlap the top 3" per side with an additional layer of foam tape.




13. Apply masking tape to the painted bumper cover at the grille opening and paint everything inside the grille opening with flat or semi-gloss black paint that would be visible through the mesh grille.




14. Thoroughly clean the factory grille surround and apply adhesive promoter to enhance the effectiveness of the double faced tape.



15. Reinstall the mesh section using the #8 x 1/2" black truss head screws, making sure it is tight against the foam tape installed in Step 12.



16. Install the supplied .045" x 1" double faced tape to the inside of the E&G ABS grille surround. One layer around the grille perimeter. **DO NOT OVERLAP THE TAPE!**



17. Peel back a small section of double faced tape backing from each installed section of .045" x 1" double faced tape installed in the previous step.
18. Carefully align the grille surround over the existing grille, making sure all edges are flush and no silver factory grille is protruding from underneath.



19. Press firmly to set the tape after the liner has been removed.



20. Finished installation.

2009 Acura TL Overlay Grille
Side Foam Tape Location Template
Part # 1402 - 0057 - 09

2009 Acura TL Overlay Grille
Bottom Foam Tape Location Template
Part # 1402 - 0058 - 09